

Reveal Compatibility Guide

Make	Model	# of Rows	Row Spacing	Brackets Required
JD	1770NT / 1775NT	12	30"	All Rows Except Row 3: 757101 In-Between ⁽¹⁾ , or 757059 Direct-Mount Row 3: 757101 In-Between ⁽¹⁾ or 757130 Universal Parallel-Arm-Mount * 757059 Direct-Mount bracket can also be used on Row 3 if the left front tab on the lower plate is trimmed off or bent flat
		16	30"	All Rows: 757101 In-Between ⁽¹⁾ or 757059 Direct-Mount
		24	30"	Rows 8,9,16,17: 757071 Pivot Row Direct Mount Rows 12, 13: 757101 In-Between ⁽¹⁾ , or 757130 Universal Parallel-Arm Mount All other Rows: 757101 In-Between ⁽¹⁾ or 757059 Direct-Mount
	DB	Various	15"-30"	Rows Behind Tires: 757063 10" Setback Mount ⁽²⁾ All other Rows: 757101 In-Between ⁽¹⁾ , or 757059 Direct-Mount, or 757130 Universal Parallel-Arm-Mount * There are multiple versions of DB frames that have various structural members and other obstructions on the frame that may interfere with the 757059 Direct-Mount bracket. * Long parallel arms can be switched for short arms on rows requiring the 10" Setback bracket.
	1760 1765	8	30"	Rows 2,7: 757130 Universal Parallel-Arm Mount All other Rows: 757101 In-Between ⁽¹⁾ or 757059 Direct-Mount * On rows 2 and 7, Reveal row cleaner unit must be mounted 1.5" lower to avoid interference with frame structure. See installation guide for details.
		12	30"	All Rows: 757101 In-Between ⁽¹⁾ or 757130 Universal Parallel-Arm Mount
	1790 1795	24	20"	Rows Behind Center Tires: 757063 10" Setback Mount ⁽²⁾ All other Rows: 757101 In-Between Mount ⁽¹⁾ or 757130 Universal Parallel-Arm Mount * Reveal is not compatible with 15"/30" row spacing 1790/1795 planters * If the planter bar is smaller than 7x7 setback brackets will be needed behind all tires
	1720 1725	8 - 16	30"-38"	Rows Behind 3-Point Hitch Connection and Innermost Wing Rows: 757063 10" Setback Mount ⁽²⁾ All other Rows: 757101 In-Between ⁽¹⁾ or 757130 Universal Parallel-Arm-Mount * Reveal is not compatible with CC 1720/1725 planters
	7200 1770 Conservation	12	30"	Select mounting kit based on planter clearance requirements * Reveal is not compatible with ground drive planters. Hydraulic drive is OK.
		16	30"	Rows 8 and 9: 757101 In-Between ⁽¹⁾ or 757130 Universal Parallel-Arm Mount All other Rows: 757101 In-Between ⁽¹⁾ or 757059 Direct-Mount * Reveal is not compatible with ground drive planters. Hydraulic drive is OK.
KZ	2600 3600 3660	All	30"	Middle 6 Rows: 757061 6" Setback Mount ⁽²⁾ All other Rows: 757101 In-Between ⁽¹⁾ or 757130 Universal Parallel-Arm-Mount * Reveal is not compatible with inter-plant pusher rows * If planter frame is smaller than 7x7, 757063 10" Setback may be required for clearance to lift frame
	3700	All	15" - 30"	Rows Behind Tires: 757063 10" Setback Mount ⁽²⁾ All other Rows: 757101 In-Between ⁽¹⁾ , or 757059 Direct-Mount, or 757130 Universal Parallel-Arm-Mount
	3800	24	30"	Rows 9-16: 757061 6" Setback Mount ⁽²⁾ All other Rows: 757101 In-Between ⁽¹⁾ , or 757059 Direct-Mount, or 757130 Universal Parallel-Arm-Mount
	4900 4905	16	30"	Rows 5, 6,11,12: 757130 Universal Parallel-Arm-Mount Rows 7-10: 757101 In-between ⁽¹⁾ or 757130 Universal Parallel-Arm-Mount All other Rows: 757101 In-between ⁽¹⁾ , 757059 Direct-Mount, or 757130 Universal Parallel-Arm-Mount
		24	30"	Rows 7-9, 16-18: 757130 Universal Parallel-Arm-Mount Rows 12, 13: 757101 In-between ⁽¹⁾ or 757130 Universal Parallel-Arm-Mount All other Rows: 757101 In-between ⁽¹⁾ , 757059 Direct-Mount, or 757130 Universal Parallel-Arm-Mount
White/ Massey	9800	12	30"	757059- all rows that don't have obstructions on toolbar
		16	30"	Rows 6,8,9,11: 757101 In-Between Mount ⁽¹⁾ or 757130 Universal Parallel-Arm Mount All other Rows: 757101 In-Between ⁽¹⁾ or 757059 Direct-Mount
		24	30"	Select mounting kit based on planter clearance requirements
PP	Precision Ready Row Unit			Select mounting kit based on planter clearance requirements
Harvest International	Harvest Planters and/or Laser Pro Row Unit	Various	15"-30"	Rows Behind Tires: 757061 6" Setback Mount ⁽²⁾ or 757063 10" Setback Mount ⁽²⁾ Rows with Obstructions on Toolbar: 757101 In-Between Mount All other Rows: 757101 In-Between ⁽¹⁾ , or 757059 Direct-Mount * Reveal is not compatible with the narrow Laser Pro row unit * 757112 Universal Parallel-Arm Mount can be used on Laser Pro row units, but only with Harvest's Dawn GFX mounting kit, which sets the row unit back roughly 4"
Case IH	1250 1255	12 - 24	30"	All Rows: 757078 Mount * 757078 Mounting Brackets set the row unit back 3.5" to provide adequate clearance to the front of the row unit (including Conceal) * Planters with any downforce system other than DeltaForce also require 757105 Downforce Bracket Spacer Kit to make up for the 3.5" setback of the row units
	2150	12 - 24	30"	All Rows: 757092 Mount

Notes:

1) 757101 In-Between Bracket moves the W-plate back 1/2" from the toolbar. This will affect hex-shaft mounting/alignment, and may not be compatible on some hex-shaft drive applications.

2) 757061 and 757063 setback-style brackets used on hex-shaft drive applications will require a jumper chain and jackshaft arrangement. See install guide for details.